

30GXN,R080-528, 30GX080-350 Accessory Security Grille Package 50/60 Hz

Installation Instructions

Part Nos.: 30GX900001

30GX900002 30GX900003 30GX900010 30GX900013

30GX900024 30GX900034

SAFETY CONSIDERATIONS

When installing this accessory, observe precautions in the literature and on any labels attached to the equipment, and all other safety precautions that may apply.

- · Follow all safety codes.
- Wear safety glasses and work gloves.
- Use care in handling and installing this accessory.



ELECTRIC SHOCK HAZARD.

Open and tag all remote disconnects before installing this equipment, to avoid the possibility of electrical shock.

INTRODUCTION

The accessory security grille packages help to prevent unit damage by debris or vandalism. See Fig. 1. The packages supplement the standard grilles on the header end of each unit to protect chiller coolers, compressors, coils, and other internal components. See Table 1 for a list of the accessory packages available for each unit size and the grilles contained in each package.




Fig. 1 — Security Grille (Typical)

INSTALLATION

- **Step 1** Inspect package contents for any missing or damaged parts. File a claim with the shipping company if any item is missing or damaged, and notify your Carrier representative.
- **Step 2** Disconnect all power to unit.
- **Step 3** Remove grilles from package. See Fig. 2-7 for location of grilles according to unit size and grille size. All grille mounting holes are predrilled in unit.
- **Step 4** Orient vertical bars on grilles toward inside of unit. For large side grilles, loosely fasten hooks at tops of grilles to top of unit using screws and washers provided. See Fig. 2-7.
- **Step 5** For small end grilles (part no. 30GX500817), loosely fasten top hooks on sides of grilles to top holes in rails underneath control box using screws and washers provided. See Fig. 2-7.
- **Step 6** For large side grilles, align bottom mounting holes between closely-spaced horizontal bars at bottom of grille. Insert screws and washers between bars and tightly fasten bottom of grille to unit.
- **Step 7** For small end grilles, align bottom set of hooks with bottom holes in end rails under control box. Fasten hooks to rails using screws and washers provided.
- **Step 8** On all grilles, tighten screws holding top grille hooks to unit.
- **Step 9** On large side grilles, use supplied wire ties to fasten adjoining grilles together approximately 18 in. from tops and bottoms of grilles. Align wire ties and clip excess material for a neat appearance.
- **Step 10** When all grilles are properly installed and fastened, restore power to unit.

7-00

Table 1 — Unit Application

UNIT SIZE	ACCESSORY PART NO.	PACKAGE CONTENTS — (Qty) PART NO., DESCRIPTION		
		(6) 30GX500815 Grille, 32 ¹ / ₄ x 71 ¹ / ₂ in. (819 x 1816 mm)		
		(2) 30GX500817 Grille, 34 ¹ / ₂ x 20 ⁵ / ₈ in. (876 x 524 mm)		
30GX080-105 30GXN,R080, 090*	30GX900001	(32) Screw, ¹ / ₄ -14 x ⁵ / ₈ in.		
30GAN,R080, 090"		(32) Washer, ³ / ₈ in.		
		(8) Wire Tie		
		(6) 30GX500816 Grille, 38 x 71 ¹ / ₂ in. (965 x 1816 mm)		
30GX106-125	30GX900002	(2) 30GX500817 Grille, 34 ¹ / ₂ x 20 ⁵ / ₈ in. (876 x 524 mm)		
30GXN,R083, 093-115,		(44) Screw, ¹ / ₄ -14 x ⁵ / ₈ in.		
125, 135*		(44) Washer, ³ / ₈ in.		
		(8) Wire Tie		
		(8) 30GX500816 Grille, 38 x 711/ ₂ in. (965 x 1816 mm)		
30GX136.150.160		(2) 30GX500817 Grille, 34 ¹ / ₂ x 20 ⁵ / ₈ in. (876 x 524 mm)		
30GXN,R118, 128, 138,	30GX900003	(56) Screw, ¹ / ₄ -14 x ⁵ / ₈ in.		
150,160*		(56) Washer, ³ / ₈ in.		
		(12) Wire Tie		
		(7) 30GX500815 Grille, 32 ¹ / ₄ x 71 ¹ / ₂ in. (819 x 1816 mm)		
		(4) 30GX500816 Grille, 38 x 71 ¹ / ₂ in. (965 x 1816 mm)		
30GX151,161,175,205,225		(2) 30GX500817 Grille, 34 ¹ / ₂ x 20 ⁵ / ₈ in. (876 x 524 mm)		
30GXN,R153, 174, 175, 204, 205, 225*	30GX900013	(52) Screw, ¹ / ₄ -14 x ⁵ / ₈ in.		
204, 205, 225"		(52) Washer, ³ / ₈ in.		
		(16) Wire Tie		
		(9) 30GX500815 Grille, 32 ¹ / ₄ x 71 ¹ / ₂ in. (819 x 1816 mm)		
		(4) 30GX500816 Grille, 38 x 71 ¹ / ₂ in. (965 x 1816 mm)		
30GX176		(2) 30GX500817 Grille, 34 ¹ / ₂ x 20 ⁵ / ₈ in. (876 x 524 mm)		
30GXN,R163, 178*	30GX900024	(68) Screw, ¹ / ₄ -14 x ⁵ / ₈ in.		
		(68) Washer, ³ / ₈ in.		
		(20) Wire Tie		
	30GX900009	(6) 30GX500815 Grille, 32 ¹ / ₄ x 71 ¹ / ₂ in. (819 x 1816 mm)		
		(7) 30GX500816 Grille, 38 x 71 ¹ / ₂ in. (965 x 1816 mm)		
30GX206,226,250		(2) 30GX500817 Grille, 34 ¹ / ₂ x 20 ⁵ / ₈ in. (876 x 524 mm)		
30GXN,R249, 250, 264*		(74) Screw, ¹ / ₄ -14 x ⁵ / ₈ in.		
, , ,		(74) Washer, ³ / ₈ in.		
		(20) Wire Tie		
		(7) 30GX500815 Grille, 32 ¹ / ₄ x 71 ¹ / ₂ in. (819 x 1816 mm)		
		(8) 30GX500816 Grille, 38 x 71 ¹ / ₂ in. (965 x 1816 mm)		
30GX251.265		(2) 30GX500817 Grille, 34 ¹ / ₂ x 20 ⁵ / ₈ in. (876 x 524 mm)		
30GXN,R208, 228*	30GX900010	(84) Screw, ¹ / ₄ -14 x ⁵ / ₈ in.		
,,		(84) Washer, ³ / ₈ in.		
		(24) Wire Tie		
		(7) 30GX500815 Grille, 32 ¹ / ₄ x 71 ¹ / ₂ in. (819 x 1816 mm)		
	30GX900034	(10) 30GX500816 Grille, 38 x 71 ¹ / ₂ in. (965 x 1816 mm)		
30GX281-350		(2) 30GX500817 Grille, 34 ¹ / ₂ x 20 ⁵ / ₈ in. (876 x 524 mm)		
30GXN,R253, 268-350*		(92) Screw, ¹ / ₄ -14 x ⁵ / ₈ in.		
		(92) Washer, ³ / ₈ in.		
		(28) Wire Tie		

^{*}And associated modular sizes. Refer to Table 2 for modular size combinations.

Table 2 — 30GXN,R Modular Combination Sizes

SIZE	MODULE A	CHASSIS SIZE	MODULE B	CHASSIS SIZE
220 (50 Hz only)	125	3	090	2
240 (50 Hz only)	125	3	115	3
275 (50 Hz only)	135	3	135	3
283 (60 Hz & 50 Hz)	153	5	138	4
300 (50 Hz only)	160	4	135	3
303 (60 Hz & 50 Hz)	163	6	138	4
320 (50 Hz only)	160	4	160	4
328 (60 Hz & 50 Hz)	178	6	153	5
345 (50 Hz only)	175	5	175	5
353 (60 Hz & 50 Hz)	178	6	178	6
365 (50 Hz only)	250	6	135	3
370 (60 Hz only)	225	5	150	4
373 (60 Hz & 50 Hz)	253	8	138	4
390 (60 Hz only)	264	6	135	3
393 (60 Hz & 50 Hz)	253	8	153	5
395 (50 Hz only)	264	6	135	3
410 (50 Hz only)	225	5	205	5
415 (60 Hz only)	264	6	160	4
418 (60 Hz & 50 Hz)	268	8	153	5
440 (50 Hz only)	225	5	225	5
450 (60 Hz only)	225	5	225	5
453 (60 Hz & 50 Hz)	228	7	228	7
470 (50 Hz only)	250	6	225	5
475 (60 Hz only)	249	6	225	5
478 (60 Hz & 50 Hz)	253	8	228	7
495 (50 Hz only)	250	6	250	6
500 (60 Hz only)	249	6	249	6
503 (60 Hz & 50 Hz)	253	8	253	8
520 (50 Hz only)	264	6	264	6
525 (60 Hz only)	264	6	264	6
528 (60 Hz & 50 Hz)	268	8	268	8






Fig. 2 — Installed Grille Locations, Sizes 080-150 and 160 (And Associated Modular Sizes)







NOTES:

SIDE VIEW FROM OIL SEPARATOR SIDE


- Header end grilles are standard on all units.
 Adjoining grilles to be wire tied together in 2 places approximately 18.0 in. from top and bottom. Align wire ties and clip excess for a neat appearance.
 Only (1) 30GX500817 is used for 30GXN,R204,225 units.
 Refer to Table 2 for modular combinations.







END VIEW

Fig. 3 — Installed Grille Locations, Sizes 151, 153, 161, 174, 175, 204, 205, 225 (And Associated Modular Sizes)






SIDE VIEW FROM OIL SEPARATOR SIDE




- NOTES:
 1. Header end grilles are standard on all units.
 2. Adjoining grilles to be wire tied together in 2 places approximately 18.0 in. from top and bottom. Align wire ties and clip excess for a neat appearance.

Fig. 4 — Installed Grille Locations, Sizes 163, 176, 178



- WIRE TIE (SEE NOTE 2) PART NO. 30GX500815 PART NO. 30GX500816 PART NO. 30GX500816 PART NO. 30GX500816 PART NO. 30GX500815

SIDE VIEW FROM OIL SEPARATOR SIDE




CONTROL BOX END VIEW

- NOTES:
 1. Header end grilles are standard on all units.
 2. Adjoining grilles to be wire tied together in 2 places approximately 18.0 in. from top and bottom. Align wire ties and clip excess for a neat appearance.

 3. Only (1) 30GX500817 is used for 30GXN,R249,250 and 264 models.


 4. Refer to Table 2 for modular size combinations.

Fig. 5 — Installed Grille Locations, Sizes 206, 226, 249, 250, 264 (And Associated Modular Sizes)



WIRE TIE (SEE NOTE 2) PART NO. 30GX500815 PART NO. 30GX500816 PART NO. 30GX500815 -- PART NO. 30GX500816 PART NO. 30GX500815 PART NO. 30GX500816


SIDE VIEW FROM OIL SEPARATOR SIDE




NOTES:


- Header end grilles are standard on all units.
 Adjoining grilles to be wire tied together in 2 places approximately 18.0 in. from top and bottom. Align wire ties and clip excess for a neat appearance.

Fig. 6 — Installed Grille Locations, Sizes 208, 228, 251, 265





SIDE VIEW FROM OIL SEPARATOR SIDE



- Header end grilles are standard on all units.
 Adjoining grilles to be wire tied together in 2 places approximately 18.0 in. from top and bottom. Align wire ties and clip excess for a neat appearance.
 Only (1) 30GX500817 is used for 30GXN,R281-350 models.

Fig. 7 — Installed Grille Locations, Sizes 253, 268-350

Copyright 2002 Carrier Corporation

Manufacturer reserves the right to discontinue, or change at any time, specifications or designs without notice and without incurring obligations.

Book 2 PC 903 Catalog No. 533-00008 Printed in U.S.A. Form 30GX-26SI Pg 12 202 7-00 Replaces: 30GX-20SI

Tab 5c